



# TECHNICAL DATASHEET

**MINIJET 80 /** REF.30973

**ATOMIZER**



Maximum working pressure	80 bar
Maximum product flow-rate	4,5 L/min
Electric motor	1,5 kW
Power	230 V / 50-60 Hz
Type of pump	volumetric screw
Pump	JET 1
Tank capacity	45 L
Max tip size	0,045"
Dimensions (L x w x h)	66 x 43 x 71 cm
Weight	53 kg
Noise level	91 Lwa

MINIJET 80 enables application of all types of pasty film fillers. It is a compact, quiet and light machine. It can be moved up and down stairs by only one person, thanks to its trolley-type chassis.

Cleaning can be made rapidly, only at the very end of the project and the pump can be changed in 5 minutes directly on the construction site.

The machine is equipped with a ball nose pump with integrated filter. Starting is wireless when the gun is opened.

The quick-release hoses make it easier to use on site.

## APPLICATIONS

All types of ready-to-use film plasters: smoothing coating, raking coating, casing coating, bituminous coating ...

## DELIVERED WITH

- a Ø16 x 10 m hose
- a spray-gun with tip holder
- a Standard 535 tip
- a toolbox containing:
  - two spanners 17 and 22
  - a multigrip plier
  - three Allen keys Ø2, 5 and 8
  - two cleaning balls and a cleaning brush
  - 1 L of storage liquid



**EUROMAIR**